

# MATERIAL SAFETY DATA SHEET

Product Name: POWER TERG 105

Product No. 099.00

## SAVIN PRODUCTS COMPANY, INC.

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: POWER TERG 105

Emergency phone: Chemtrec: 800-424-9300

Product Information: 781-961-2744

Company: SAVIN PRODUCTS COMPANY, INC.

214 HIGH STREET  
RANDOLPH, MA 02368

Date Prepared: 12-09-03

Supersedes: 10-02-00

Prepared by: KJS

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No.	Exposure Limits	Typical % by Weight
1. Potassium Hydroxide	1310-58-3	ACGIH TLV ppm; 2 mg/m <sup>3</sup> (Ceiling) OSHA PEL: None	1 - 5
2. Nonylphenol Ethoxylate	9016-58-3	N/A	1 - 5
3. Tetrasodium salt of Ethylenediamine tetraacetic acid	64-02-8	N/A	1 - 5

### 3. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

**WARNING:** Severe eye irritant. May cause burns.. May cause skin irritation with prolonged contact. Inhalation of mist can cause damage to respiratory tract. Harmful if swallowed. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Avoid breathing mist.. Do not take internally.

EFFECTS of OVEREXPOSURE:

CARCINOGENICITY:

NTP: No

IARC: No

OSHA: No

EYES: May cause severe eye irritation.

SKIN: Repeated or prolonged contact may cause skin irritation.

INHALATION: Mist may cause irritation to mucous membranes and respiratory tract.

INGESTION: May result in gastric distress and nausea. May cause burns to GI tract.

CHRONIC EFFECTS and MEDICAL CONDITIONS: The effects of long-term, low-level exposures to this product have not been determined. Safe handling of this material on a long-term basis should emphasize the avoidance of all effects from repetitive acute exposure. This product may aggravate existing eye, skin and respiratory conditions.

### 4. FIRST AID MEASURES

EYES: Flush with copious amounts of water for at least 15 minutes, lifting upper and lower lids occasionally. Get immediate medical attention.

SKIN: Immediately flush with water. Remove contaminated clothing. Launder contaminated clothing before reuse.

INHALATION: Remove to fresh air. If breathing is difficult, oxygen may be given, preferably with a physician's advice. If not breathing, give artificial. Get medical attention.

INGESTION: If swallowed, give several glasses of water. Do not induce vomiting. If vomiting does occur, give fluids again and keep head below hips to help prevent aspiration. Do not give anything by mouth to an unconscious person. Get immediate medical attention.

# MATERIAL SAFETY DATA SHEET

Product Name: POWER TERG 105

Product No. 099.00

## 5. FIRE FIGHTING MEASURES

### FLAMMABLE PROPERTIES:

Flash Point: >200°F Test: SETA CC ASTM D3278

Explosive Limits: LEL: N/A UEL: N/A

EXTINGUISHING MEDIA: Not combustible under test conditions. However evaporated water may leave a combustible product classified IIIB by NFPA/OSHA.

SPECIAL PROCEDURES & UNUSUAL HAZARDS: Very slippery under foot. Very foam when mixed with water. Alkaline mixture.

FIREFIGHTING INSTRUCTIONS: Firefighters should wear NIOSH approved, positive pressure, self-contained breathing apparatus and full protective clothing when appropriate.

## 6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS: Soak up small spills with inert solids. Use suitable disposal container. Or neutralize with vinegar and discharge to sewer.

LARGE SPILLS: Limit access to area. Dike and contain spill with inert material (sand, earth, etc.) and transfer the liquid and solid separately to containers for recovery or disposal. Keep spill out of sewers and open bodies of water.

CAUTION: Floor may become slippery in the spill area.

## 7. HANDLING AND STORAGE

Handle according to good manufacturing and warehousing practices. Use good personal hygiene practices. Wash hand before eating, drinking, smoking or using toilet facilities. Promptly remove soiled clothing and wash thoroughly before reuse. Store only in tightly closed containers away from heat. Always add product to water when diluting is call for. Do not use aluminum containers. Have contingency information posted in the use & storage area.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION: Avoid splashing. Wear chemical-resistant safety goggles if necessary. Contact lenses must not be worn.

PROTECTIVE GLOVES: Depending on conditions of use, protective gloves, apron, boots, head and face protection should be worn. This equipment should be cleaned thoroughly after each use.

RESPIRATORY PROTECTION: Avoid inhaling spray, mist or dust. Where exposure through inhalation may occur from use, NIOSH/MSHA approved respiratory protection equipment is recommended.

VENTILATION: Ventilation is required in case of mist conditions. Either local exhaust or general room ventilation is usually adequate.

OTHER PROTECTIVE EQUIPMENT: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Clear, green, thin, foamy liquid.

BOILING POINT: approx. 212-220°F @ 1ATM

FREEZE/MELT POINT: approx. 32°F

VAPOR PRESSURE (mm): ca 17 mm Hg @ 70°F

VAPOR DENSITY (air=1): ca water.

EVAPORATION RATE: ca water

SOLUBILITY IN WATER: Complete.

SPECIFIC GRAVITY: 1.05 @ 20°C

DENSITY: 8.75 lb/gal

pH( as is ): 13.7

ODOR: Mild.

ODOR THRESHOLD (ppm): Not determined.

## 10. STABILITY AND REACTIVITY

CHEMICAL STABILITY : Stable.

INCOMPATIBILITY: Strong acids, strong oxidizers and excessive heat.

HAZARDOUS DECOMPOSITION PRODUCTS: Explosive Hydrogen gas may generate upon contact with aluminum, zinc or tin.

HAZARDOUS POLYMERIZATION: None

# MATERIAL SAFETY DATA SHEET

Product Name: POWER TERG 105

Product No. 099.00

## 11. TOXICOLOGICAL INFORMATION

No LD50 or LC50 found for oral, dermal or inhalation routes of administration.

## 12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL/CHEMICAL FATE INFORMATION: Toxic to aquatic life.

## 13. DISPOSAL CONSIDERATIONS

RCRA: This product, if disposed as shipped, is considered a hazardous waste as specified in 40 CFR 261.22. Dilute solutions of this product with a pH of <12.5 are not classified as hazardous waste.

Dispose in accordance with all applicable federal, state and local regulations.

## 14. TRANSPORT INFORMATION

SHIPPING NAME: CLEANING COMPOUND, LIQUID  
HAZARD CLASS: Not Regulated as a Hazardous Material  
ID #: N/A  
PACKING GROUP: N/A  
LABEL: N/A

## 15. REGULATORY INFORMATION

This material does not contain nor was it manufactured using ozone-depleting chemicals.

### U.S. FEDERAL REGULATIONS:

TSCA STATUS: All ingredients on Toxic Substance Control Act Inventory.

CERCLA REPORTABLE QUANTITY: Potassium Hydroxide (1000 lbs)

### SARA TITLE III:

Section 302 Extremely Hazardous Substances:	None.
Section 311/312 Hazardous Categories:	Immediate (Acute)
Section 313 Toxic Chemicals:	None.

## 16. OTHER INFORMATION

All label precautions must be observed when handling, storing and transporting empty containers due to product residues. Do not reuse this container unless it is professionally cleaned and reconditioned.

### REFERENCES:

- U.S. Dept. of Health and Human Services, NIOSH: Registry of Toxic Effects of Chemical Substances, 1985-86 Editions.
- Sax, N. Irving and Lewis, R.J.: Dangerous Properties of Industrial Materials, 7th Edition, Van Nostrand Reinhold Co., 1989.
- Lewis, R.J.: Hawley's Condensed Chemical Dictionary, 12th Edition, Van Nostrand Reinhold Co., 1993.
- U.S. Dept. of Transportation, U.S. Coast Guard: CHRIS Hazardous Chemical Data, 1982.
- U.S. Dept. of Labor, OSHA: Air Contaminants - Permissible Exposure Limits, 1989.
- National Fire Protection Association (NFPA): Fire Protection Guide on Hazardous Materials (NFPA 325M/49/491M/704), 9th Edition, 1986.
- National Fire Protection Association (NFPA): Hazardous Materials Response Handbook, Henry, M.F., Editor, 1989.
- Merck & Co., Inc.: The Merck Index, 11th Edition, 1989.

Information herein is given in good faith as authoritative and valid; no warranty, express or implied can be made.